

in writing as a condition for the endorsement by the Commandant (GMSO).

[CGD 81-101, 53 FR 28974, Aug. 1, 1988. Redesignated at CGD 84-043, 55 FR 37411, Sept. 11, 1990, and amended by CGD 84-043, 55 FR 37412, Sept. 11, 1990; CGD 95-072, 60 FR 50464, Sept. 29, 1995; CGD 96-041, 61 FR 50730, Sept. 27, 1996]

§ 98.30-15 Leakage containment.

(a) No person may transfer a product to or from a vessel unless there is a container or enclosed deck area that meets the requirements of this section under or around each transfer connection area.

(b) Each container or enclosed deck area must hold, in all conditions of vessel list or trim to be encountered during the transferring operation, 5 gallons or more and must have a means of draining or removing any leakage without mixing incompatible products or discharging into the water.

§ 98.30-17 Qualifications of person in charge.

(a) The operator or agent of each vessel shall designate the person in charge of a transfer of liquid cargo in bulk to or from a portable tank.

(b) Each person designated as person in charge of a transfer of liquid cargo in bulk to or from a portable tank shall—

(1) On a tank barge, hold a “Tankerman-PIC”, restricted “Tankerman-PIC”, “Tankerman-PIC (Barge)”, or restricted “Tankerman-PIC (Barge)” merchant mariner’s document authorizing transfer of the classification of cargo involved;

(2) On a self-propelled tank vessel, or on a tankship, carrying oil or hazardous material in bulk, hold a valid license or certificate authorizing service as a master, mate, pilot, engineer, or operator aboard that vessel, and a Tankerman-PIC or a restricted Tankerman (PIC) endorsement on his or her MMD.

[CGD 79-116, 60 FR 17157, Apr. 4, 1995, as amended at 62 FR 25135, May 8, 1997]

§ 98.30-19 Supervision by person in charge.

(a) No person may connect, top off, disconnect, or engage in any other crit-

ical product transfer operation unless the person in charge designated in § 98.30-17, personally supervises the operation.

(b) No person may start the flow of a product to or from a portable tank unless instructed to do so by the person in charge.

(c) No person may transfer a product to or from a portable tank unless the person in charge is in the immediate vicinity of the transfer operation and immediately available to the person transferring the product.

§ 98.30-21 Inspection prior to transfer.

No person may transfer to or from a portable tank a product with a flashpoint of less than 300° F unless the person in charge of the transfer determines that—

(a) Each warning signal and sign required in §§ 98.30-33 and 98.30-35 is displayed;

(b) No repair work in the vicinity of any portable tank is done without permission of the person in charge of the transfer operation; and

(c) Riveting, welding, burning, or a similar operation is not done in the vicinity of a portable tank unless an inspection by the person in charge of the transfer ensures that the operation can be done safely.

§ 98.30-23 Requirements for transfer; general.

No person may transfer a product to or from a portable tank unless—

(a) The vessel’s moorings are strong enough to hold in all expected conditions of surge, current, and weather and are long enough to allow adjustment for changes in draft, drift, and tide during the transfer operation;

(b) Transfer hoses or loading arms are long enough to allow the vessel to move the limits of its mooring without placing strain on the hose, loading arm, or transfer piping system;

(c) Each transfer hose is supported in a manner that prevents strain on its coupling;

(d) Each part of the transfer system necessary to allow the flow of the product is lined up for the transfer;

(e) Each transfer hose has no loose covers, kinks, bulges, soft spots, and no